


料号 Part NO.	品名 Parts Name	型号 Part NO.	Approx. Length (mm)	Approx. Width (mm)	Max. Bundle Dia. (mm)	Min. Loop Tensile Strenght (kg)	包装 packing	相关认证
31-HIWA-GT-1370HDL	束线带S	GT-1370HDL	1370	9.0	412	79.4		



材质: 采用UL认证材料66, 防火等级94V-2, 阻燃,
耐酸碱, 绝缘性好, 不变色, 承受力强。

温度: 可达85℃。

颜色: 各种颜色皆可定制

技术要求:

有光泽, 手感好, 无掉齿
无封洞, 无气泡



DIMENSION	TOLERANCES	REVISION RECORD				DWG. BY		CHK. BY		DATE
		LTR.	NEW PART	DWG. BY	CHK. BY	DATE				
0.0 0.00	±0.2	A	NEW PART	william	yan wang	2008				
FIRST ANGLE PROJ										
DWG. BY	<i>Lin Liang</i>	UNIT	mm							
CHK. BY	<i>william</i>	REV.	A							
APP. BY	<i>wang yan</i>	DWG. NO.	HIWA/OR-JZ-31-HIWA-1370HDL							

未经并受权不得修改和复印
该知识产属于技术质量部

HIWA 惠州惠华电子科技有限公司